


# GK20PI60T5H

## IGBT Module

### Features:

- Non Punch Through (NPT) Technology
- Short Circuit Rated >10 $\mu$ s
- Low Saturation Voltage
- Low Switching Loss
- 100% RBSOA Tested(2 $\times$ I<sub>c</sub>)
- Low Stray Inductance
- Lead Free, Compliant with RoHS Requirement



### Applications:

- Industrial Inverters

### IGBT, Inverter

#### Maximum Rated Values (T<sub>C</sub>=25 $^{\circ}$ C unless otherwise specified)

V <sub>CES</sub>	Collector-Emitter Blocking Voltage		600	V
V <sub>GES</sub>	Gate-Emitter Voltage		$\pm$ 20	V
I <sub>C</sub>	Continuous Collector Current	T <sub>C</sub> =80 $^{\circ}$ C	20	A
		T <sub>C</sub> =25 $^{\circ}$ C	40	A
I <sub>CM</sub>	Repetitive Peak Collector Current	T <sub>J</sub> =150 $^{\circ}$ C	40	A
t <sub>SC</sub>	Short Circuit Withstand Time		>10	$\mu$ s
P <sub>D</sub>	Maximum Power Dissipation per IGBT	T <sub>C</sub> =25 $^{\circ}$ C T <sub>Jmax</sub> =150 $^{\circ}$ C	156	W

## Electrical Characteristics of IGBT ( $T_C=25^\circ\text{C}$ unless otherwise specified)

### Static Characteristics

Symbol	Description	Conditions	Min	Typ	Max	Unit
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=1\text{mA}$ , $V_{CE}=V_{GE}$	4.0	4.8	5.8	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=20\text{A}$ , $V_{GE}=15\text{V}$	$T_J=25^\circ\text{C}$	2.00		V
			$T_J=125^\circ\text{C}$		2.15	V
$I_{CES}$	Collector-Emitter Leakage Current	$V_{GE}=0\text{V}$ , $V_{CE}=V_{CES}$ , $T_J=25^\circ\text{C}$			1	mA
$I_{GES}$	Gate-Emitter Leakage Current	$V_{GE}=\pm 20\text{V}$ , $V_{CE}=0\text{V}$ , $T_J=25^\circ\text{C}$			200	nA
$C_{ies}$	Input Capacitance	$V_{CE}=25\text{V}$ , $V_{GE}=0\text{V}$ , $f=100\text{kHz}$		1.33		nF
$C_{oes}$	Output Capacitance			0.16		nF
$C_{res}$	Reverse Transfer Capacitance			0.04		nF

### Switching Characteristics

$t_{d(on)}$	Turn-on Delay Time	$V_{CC}=300\text{V}$ , $I_C=20\text{A}$ , $R_{Gon}=30\Omega$ , $V_{GE}=\pm 15\text{V}$ , Inductive Load	$T_J=25^\circ\text{C}$		88	ns
			$T_J=125^\circ\text{C}$		96	
$t_r$	Rise Time	$V_{CC}=300\text{V}$ , $I_C=20\text{A}$ , $R_{Gon}=30\Omega$ , $V_{GE}=\pm 15\text{V}$ , Inductive Load	$T_J=25^\circ\text{C}$		28	ns
			$T_J=125^\circ\text{C}$		29	
$t_{d(off)}$	Turn-off Delay Time	$V_{CC}=300\text{V}$ , $I_C=20\text{A}$ , $R_{Goff}=30\Omega$ , $V_{GE}=\pm 15\text{V}$ , Inductive Load	$T_J=25^\circ\text{C}$		158	ns
			$T_J=125^\circ\text{C}$		164	
$t_f$	Fall Time	$V_{CC}=300\text{V}$ , $I_C=20\text{A}$ , $R_{Goff}=30\Omega$ , $V_{GE}=\pm 15\text{V}$ , Inductive Load	$T_J=25^\circ\text{C}$		129	ns
			$T_J=125^\circ\text{C}$		167	
$E_{on}$	Turn-on Switching Loss	$V_{CC}=300\text{V}$ , $I_C=20\text{A}$ , $R_{Gon}=30\Omega$ , $V_{GE}=\pm 15\text{V}$ , $di/dt=559\text{A}/\mu\text{s}$ ( $T_J=125^\circ\text{C}$ ) Inductive Load	$T_J=25^\circ\text{C}$		0.48	mJ
			$T_J=125^\circ\text{C}$		0.56	
$E_{off}$	Turn-off Switching Loss	$V_{CC}=300\text{V}$ , $I_C=20\text{A}$ , $R_{Goff}=30\Omega$ , $V_{GE}=\pm 15\text{V}$ , $du/dt=3121\text{V}/\mu\text{s}$ ( $T_J=125^\circ\text{C}$ ) Inductive Load	$T_J=25^\circ\text{C}$		0.22	mJ
			$T_J=125^\circ\text{C}$		0.36	
$Q_g$	Total Gate Charge	$V_{GE}=+15\text{V}\dots-15\text{V}$	$T_J=25^\circ\text{C}$		121	nC
RBSOA	$I_C=40\text{A}$ , $V_{CC}=480\text{V}$ , $V_p=600\text{V}$ , $R_{Goff}=30\Omega$ , $V_{GE}=+15\text{V}$ to $0\text{V}$ , $T_J=125^\circ\text{C}$			Trapezoid		
SCSOA	$V_{CC}=300\text{V}$ , $V_{GE}=15\text{V}$ , $T_J=125^\circ\text{C}$			10		$\mu\text{s}$
$R_{\theta JC}$	IGBT Thermal Resistance: Junction-To-Case(Per Leg)				0.80	$^\circ\text{C}/\text{W}$

### Diode, Inverter

#### Maximum Rated Values ( $T_C=25^\circ\text{C}$ unless otherwise specified)

$V_{RRM}$	Repetitive Peak Reverse Voltage	600	V
$I_F$	Diode Continuous Forward Current	20	A
$I_{FM}$	Diode Maximum Forward Current	40	A

#### Electrical Characteristics of Diode ( $T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Description	Conditions	Min	Typ	Max	Unit
$V_{FM}$	Forward Voltage	$I_F=20\text{A}$	$T_J=25^\circ\text{C}$	1.50		V
			$T_J=125^\circ\text{C}$	1.55		
$I_{rr}$	Peak Reverse Recovery Current	$I_F=20\text{A}$ , $-diF/dt=227\text{A}/\mu\text{s}(T_J=125^\circ\text{C})$ , $V_{rr}=300\text{V}$ , $V_{GE}=-15\text{V}$	$T_J=25^\circ\text{C}$	15.3		A
			$T_J=125^\circ\text{C}$	18.4		
$Q_{rr}$	Reverse Recovery Charge		$T_J=25^\circ\text{C}$	0.94		$\mu\text{C}$
			$T_J=125^\circ\text{C}$	1.41		
$E_{rec}$	Reverse Recovery Energy		$T_J=25^\circ\text{C}$	0.14		mJ
			$T_J=125^\circ\text{C}$	0.31		
$R_{\theta JC}$	Diode Thermal Resistance: Junction-To-Case(Per Leg)				1.75	$^\circ\text{C}/\text{W}$

### IGBT, Brake-Chopper

#### Maximum Rated Values ( $T_C=25^\circ\text{C}$ unless otherwise specified)

$V_{CES}$	Collector-Emitter Blocking Voltage		600	V
$V_{GES}$	Gate-Emitter Voltage		$\pm 20$	V
$I_C$	Continuous Collector Current	$T_C=80^\circ\text{C}$	20	A
		$T_C=25^\circ\text{C}$	40	A
$I_{CM}$	Repetitive Peak Collector Current	$T_J=150^\circ\text{C}$	40	A
$t_{SC}$	Short Circuit Withstand Time		$>10$	$\mu\text{s}$
$P_D$	Maximum Power Dissipation per IGBT	$T_C=25^\circ\text{C}$ $T_{Jmax}=150^\circ\text{C}$	156	W

## Electrical Characteristics of IGBT ( $T_C=25^\circ\text{C}$ unless otherwise specified)

### Static characteristics

Symbol	Description	Conditions	Min	Typ	Max	Unit
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=1\text{mA}, V_{CE}=V_{GE}$	4.0	4.8	5.8	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=20\text{A}, V_{GE}=15\text{V}$	$T_J=25^\circ\text{C}$	2.00		V
			$T_J=125^\circ\text{C}$		2.15	V
$I_{CES}$	Collector-Emitter Leakage Current	$V_{GE}=0\text{V}, V_{CE}=V_{CES}, T_J=25^\circ\text{C}$			1	mA
$I_{GES}$	Gate-Emitter Leakage Current	$V_{GE}=\pm 20\text{V}, V_{CE}=0\text{V}, T_J=25^\circ\text{C}$			200	nA
$C_{ies}$	Input Capacitance	$V_{CE}=25\text{V}, V_{GE}=0\text{V}, f=100\text{kHz}$		1.33		nF
$C_{oes}$	Output Capacitance			0.16		nF
$C_{res}$	Reverse Transfer Capacitance			0.04		nF

### Switching Characteristics

$t_{d(on)}$	Turn-on Delay Time	$V_{CC}=300\text{V}, I_C=20\text{A}, R_{Gon}=30\Omega, V_{GE}=\pm 15\text{V},$ Inductive Load	$T_J=25^\circ\text{C}$		88	ns	
			$T_J=125^\circ\text{C}$		96		
$t_r$	Rise Time		$T_J=25^\circ\text{C}$		28	ns	
			$T_J=125^\circ\text{C}$		29		
$t_{d(off)}$	Turn-off Delay Time		$V_{CC}=300\text{V}, I_C=20\text{A}, R_{Goff}=30\Omega, V_{GE}=\pm 15\text{V},$ Inductive Load	$T_J=25^\circ\text{C}$		158	ns
				$T_J=125^\circ\text{C}$		164	
$t_f$	Fall Time	$T_J=25^\circ\text{C}$			129	ns	
		$T_J=125^\circ\text{C}$			167		
$E_{on}$	Turn-on Switching Loss	$V_{CC}=300\text{V}, I_C=20\text{A}, R_{Gon}=30\Omega, V_{GE}=\pm 15\text{V},$ $di/dt=559\text{A}/\mu\text{s} (T_J=125^\circ\text{C})$ Inductive Load		$T_J=25^\circ\text{C}$		0.48	mJ
				$T_J=125^\circ\text{C}$		0.56	
$E_{off}$	Turn-off Switching Loss		$T_J=25^\circ\text{C}$		0.22	mJ	
			$T_J=125^\circ\text{C}$		0.36		
$Q_g$	Total Gate Charge		$V_{GE}=+15\text{V}\dots-15\text{V}$	$T_J=25^\circ\text{C}$		121	nC
RBSOA	$I_C=40\text{A}, V_{CC}=480\text{V}, V_p=600\text{V}, R_{Goff}=30\Omega, V_{GE}=+15\text{V to }0\text{V}, T_J=125^\circ\text{C}$			Trapezoid			
SCSOA	$V_{CC}=300\text{V}, V_{GE}=15\text{V}, T_J=125^\circ\text{C}$			10		$\mu\text{s}$	
$R_{\theta JC}$	IGBT Thermal Resistance: Junction-To-Case(Per Leg)				0.80	$^\circ\text{C}/\text{W}$	

### Diode, Brake-Chopper

#### Maximum Rated Values ( $T_C=25^\circ\text{C}$ unless otherwise specified)

$V_{RRM}$	Repetitive Peak Reverse Voltage	600	V
$I_F$	Diode Continuous Forward Current	10	A
$I_{FM}$	Diode Maximum Forward Current	20	A

#### Electrical Characteristics of Diode ( $T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Description	Conditions	Min	Typ	Max	Unit
$V_{FM}$	Forward Voltage	$I_F=10\text{A}$	$T_J=25^\circ\text{C}$	1.55		V
			$T_J=125^\circ\text{C}$	1.55		
$I_{rr}$	Peak Reverse Recovery Current	$I_F=10\text{A}$ , $-diF/dt = 1066\text{A}/\mu\text{s}(T_J=125^\circ\text{C})$ , $V_{rr}=300\text{V}$ , $V_{GE}=-15\text{V}$	$T_J=25^\circ\text{C}$	26.9		A
			$T_J=125^\circ\text{C}$	28.4		
$Q_{rr}$	Reverse Recovery Charge		$T_J=25^\circ\text{C}$	0.47		$\mu\text{C}$
			$T_J=125^\circ\text{C}$	0.67		
$E_{rec}$	Reverse Recovery Energy		$T_J=25^\circ\text{C}$	0.05		mJ
			$T_J=125^\circ\text{C}$	0.10		
$R_{\theta JC}$	Diode Thermal Resistance: Junction-To-Case(Per Leg)				2.13	$^\circ\text{C}/\text{W}$

### Diode, Rectifier

#### Maximum Rated Values ( $T_C=25^\circ\text{C}$ unless otherwise specified)

$V_{RRM}$	Repetitive Peak Reverse Voltage	$T_J=25^\circ\text{C}$	1600	V
$I_{FRMSM}$	Maximum RMS Forward Current per Chip	$T_J=80^\circ\text{C}$	20	A
$I_{RMSM}$	Maximum RMS Current at Rectifier Output	$T_J=80^\circ\text{C}$	30	A
$I_{FSM}$	Surge Current @ $t_p=10\text{ ms}$	$T_J=25^\circ\text{C}$	300	A
		$T_J=150^\circ\text{C}$	250	
$I^2t$	$I^2t$ - value	$T_J=25^\circ\text{C}$	450	$\text{A}^2\text{s}$
		$T_J=150^\circ\text{C}$	300	

### Electrical Characteristics of Diode ( $T_C=25^{\circ}\text{C}$ unless otherwise specified)

Symbol	Description	Conditions		Min	Typ	Max	Unit
$V_F$	Forward Voltage	$I_F=20\text{ A}$	$T_J=25^{\circ}\text{C}$		1.20		V
			$T_J=150^{\circ}\text{C}$		1.20		
$I_R$	Reverse Current	$V_R=1200\text{V}$	$T_J=25^{\circ}\text{C}$			50	$\mu\text{A}$
$R_{\theta JC}$	Diode Thermal Resistance: Junction-To-Case					1.02	$^{\circ}\text{C}/\text{W}$

### Internal NTC-Thermistor Characteristics

$R_{25}$	$T_C=25^{\circ}\text{C}$	5		$\text{k}\Omega$
$\Delta R/R$	$T_C=100^{\circ}\text{C}$ , $R_{100}=481\Omega$		$\pm 5$	%
$P_{25}$	$T_C=25^{\circ}\text{C}$	50		mW
$B_{25/50}$	$R_2=R_{25} \exp[B_{25/50}(1/T_2-1/(298.15\text{K}))]$	3380		K
$B_{25/80}$	$R_2=R_{25} \exp[B_{25/80}(1/T_2-1/(298.15\text{K}))]$	3440		K

### Module

Symbol	Description		Min	Typ	Max	Unit
$V_{iso}$	Isolation Voltage(All Terminals Shorted)	$f=50\text{Hz}$ , 1minute	2500			V
$T_J$	Maximum Junction Temperature				150	$^{\circ}\text{C}$
$T_{JOP}$	Maximum Operating Junction Temperature Range		-40		+150	$^{\circ}\text{C}$
$T_{stg}$	Storage Temperature		-40		+125	$^{\circ}\text{C}$
CTI	Comparative Tracking Index		200			
$R_{\theta CS}$	Case-To-Sink Thermally (Conductive Grease Applied)				0.04	$^{\circ}\text{C}/\text{W}$
M	Mounting Screw:M5		3.0		6.0	N·m
G	Weight			200		g

## Ordering Information Table

Device code	G	K	20	PI	60	T5	H
	①	②	③	④	⑤	⑥	⑦

- ① - IGBT Module
- ② - Non Punch Through (NPT) Technology
- ③ - Rated Current (20=20A)
- ④ - Circuit Configuration (Power Integrated)
- ⑤ - Rated Voltage (60=600V)
- ⑥ - Package Type
- ⑦ - Test Level (Pass the Important Reliability Test-Industrial Grade)

SilverMicro




Fig.1 Typical Saturation Voltage Characteristics




Fig.2 Typical Output Characteristics




Fig.3 Forward Characteristics of Diode




Fig.4 Reverse Bias Safe Operation Area (RBSOA)






Fig.5 Typical Switching Loss vs. Collector Current




Fig.6 Typical Switching Loss vs. Gate Resistance




Fig.7 Typical Saturation Voltage Characteristics (Brake-Chopper)




Fig.8 Forward Characteristics of Diode (Brake-Chopper)




Fig.9 Capacitance Characteristics




Fig.10 Forward Characteristics of Diode (Rectifier)




Fig.11 Transient Thermal Impedance IGBT (Inverter)




Fig.12 Transient Thermal Impedance Diode (Inverter)







Fig.13 NTC Temperature Characteristics

SilverMicro

### Internal Circuit



### Package Outline (Unit: mm):



\*=all dimensions with tolerance of  $\pm 0.4$



Date	Revision	Notes
01/18/2022	01	Initial Release
02/17/2022	02	Updated the Q <sub>g</sub> value
02/24/2022	A	Final Version

## Announcement

Information in this document is believed to be accurate and reliable. However, NJSME does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

## Right to Make Changes

NJSME reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

The datasheet with "REV." + "Arabic numerals" is based on engineering data for initial reference purpose only.

The released datasheet would be issued with "REV." + "alphabet characters".