


GT15PI120C7H

IGBT Module

Preliminary Data

Features:

- Trench IGBT Technology
- Short Circuit Rated > 10 μ s
- Low Saturation Voltage
- Low Switching Loss
- 100% RBSOA Tested (2 \times I_c)
- Low Stray Inductance
- Lead Free, Compliant with RoHS Requirement



Applications:

- Industrial Inverters
- Servo Applications

IGBT, Inverter

Maximum Rated Values (T_C=25°C unless otherwise specified)

V _{CES}	Collector-Emitter Blocking Voltage		1200	V
V _{GES}	Gate-Emitter Voltage		±20	V
I _C	Continuous Collector Current	T _C = 100°C	15	A
		T _C = 25°C	30	A
I _{CM(1)}	Peak Collector Current Repetitive	T _J = 175°C	30	A
t _{SC}	Short Circuit Withstand Time		>10	μs
P _D	Maximum Power Dissipation per IGBT	T _C = 25°C T _{Jmax} = 175°C	205	W

Electrical Characteristics of IGBT ($T_C=25^\circ\text{C}$ unless otherwise specified)

Static Characteristics

Symbol	Description	Conditions	Min	Typ	Max	Unit
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C = 1 \text{ mA}, V_{CE} = V_{GE}$	4.5	5.5	6.5	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C = 15\text{A}, V_{GE} = 15\text{V}$	$T_J = 25^\circ\text{C}$	1.90	2.20	V
			$T_J = 125^\circ\text{C}$	2.20		V
I_{CES}	Collector-Emitter Leakage Current	$V_{GE} = 0\text{V}, V_{CE} = V_{CES}, T_J = 25^\circ\text{C}$			1	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE} = \pm 20\text{V}, V_{CE} = 0\text{V}, T_J = 25^\circ\text{C}$			200	nA
C_{ies}	Input Capacitance	$V_{CE} = 25\text{V}, V_{GE} = 0\text{V}, f = 1\text{MHz}$		2.0		nF
C_{Oes}	Output Capacitance			0.10		nF

Switching Characteristics

$t_{d(on)}$	Turn-on Delay Time	$V_{CC} = 600\text{V}, I_C = 15\text{A}, R_{Gon} = 40\Omega, V_{GE} = \pm 15\text{V},$ Inductive Load	$T_J = 25^\circ\text{C}$		175		ns
			$T_J = 125^\circ\text{C}$		160		
t_r	Rise Time		$T_J = 25^\circ\text{C}$		50		ns
			$T_J = 125^\circ\text{C}$		55		
$t_{d(off)}$	Turn-off Delay Time	$V_{CC} = 600\text{V}, I_C = 15\text{A}, R_{Goff} = 40\Omega, V_{GE} = \pm 15\text{V},$ Inductive Load	$T_J = 25^\circ\text{C}$		140		ns
			$T_J = 125^\circ\text{C}$		145		
t_f	Fall Time		$T_J = 25^\circ\text{C}$		245		ns
			$T_J = 125^\circ\text{C}$		380		
E_{on}	Turn-on Switching Loss	$V_{CC} = 600\text{V}, I_C = 15\text{A}, R_{Gon} = 40\Omega, V_{GE} = \pm 15\text{V},$ $di/dt = 255\text{A}/\mu\text{s} (T_J = 125^\circ\text{C}),$ Inductive Load	$T_J = 25^\circ\text{C}$		1.74		mJ
			$T_J = 125^\circ\text{C}$		2.08		
E_{off}	Turn-off Switching Loss		$T_J = 25^\circ\text{C}$		0.63		mJ
			$T_J = 125^\circ\text{C}$		1.09		
Q_g	Total Gate Charge	$V_{GE} = +15\text{V} \dots -15\text{V}$	$T_J = 25^\circ\text{C}$		140		nC
RBSOA	Reverse Bias Safe Operation Area	$I_C = 30\text{A}, V_{CC} = 1050\text{V}, V_p = 1200\text{V}, R_g = 40\Omega, V_{GE} = +15\text{V to } 0\text{V}, T_J = 175^\circ\text{C}$		Trapezoid			
SCSOA	Short Circuit Safe Operation Area	$V_{CC} = 600\text{V}, V_{GE} = 15\text{V}, T_J = 150^\circ\text{C}$		10			μs
$R_{\theta JC}$	IGBT Thermal Resistance: Junction-To-Case				0.73		$^\circ\text{C}/\text{W}$

Diode, Inverter
Maximum Rated Values ($T_C=25^\circ\text{C}$ unless otherwise specified)

V_{RRM}	Repetitive Peak Reverse Voltage	1200	V
I_F	Diode Continuous Forward Current	15	A
I_{FM}	Repetitive Peak Forward Current	30	A

Electrical Characteristics of FWD ($T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Description	Conditions	Min	Typ	Max	Unit
V_{FM}	Forward Voltage	$I_F=15\text{A}$	$T_J=25^\circ\text{C}$	2.00		V
			$T_J=125^\circ\text{C}$	2.20		
I_{rr}	Peak Reverse Recovery Current		$T_J=25^\circ\text{C}$	12		A
			$T_J=125^\circ\text{C}$	15		
Q_{rr}	Reverse Recovery Charge	$I_F=15\text{A}$, $-di_F/dt = 313\text{A}/\mu\text{s}(T_J=125^\circ\text{C})$, $V_R=600\text{V}$, $V_{GE}=-15\text{V}$	$T_J=25^\circ\text{C}$	0.94		μC
			$T_J=125^\circ\text{C}$	1.64		
E_{rec}	Reverse Recovery Energy		$T_J=25^\circ\text{C}$	0.37		mJ
			$T_J=125^\circ\text{C}$	0.76		
$R_{\theta JC}$	Diode Thermal Resistance: Junction-To-Case			1.19		$^\circ\text{C}/\text{W}$

IGBT, Brake-Chopper
Maximum Rated Values ($T_C=25^\circ\text{C}$ unless otherwise specified)

V_{CES}	Collector-Emitter Blocking Voltage		1200	V
V_{GES}	Gate-Emitter Voltage		± 20	V
I_C	Continuous Collector Current	$T_C = 100^\circ\text{C}$	15	A
		$T_C = 25^\circ\text{C}$	30	A
I_{CM}	Peak Collector Current Repetitive	$T_J = 175^\circ\text{C}$	30	A
t_{SC}	Short Circuit Withstand Time		>10	μs
P_D	Maximum Power Dissipation (IGBT)	$T_C = 25^\circ\text{C}$ $T_{Jmax}=175^\circ\text{C}$	205	W

Electrical Characteristics of IGBT ($T_C=25^\circ\text{C}$ unless otherwise specified)

Static Characteristics

Symbol	Description	Conditions	Min	Typ	Max	Unit
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C = 1 \text{ mA}, V_{CE} = V_{GE}$	4.5	5.5	6.5	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C = 15 \text{ A}, V_{GE} = 15 \text{ V}$	$T_J = 25^\circ\text{C}$	1.90	2.10	V
			$T_J = 125^\circ\text{C}$	2.20		V
I_{CES}	Collector-Emitter Leakage Current	$V_{GE} = 0 \text{ V}, V_{CE} = V_{CES}, T_J = 25^\circ\text{C}$			1	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE} = \pm 20 \text{ V}, V_{CE} = 0 \text{ V}, T_J = 25^\circ\text{C}$			200	nA
C_{ies}	Input Capacitance	$V_{CE} = 25 \text{ V}, V_{GE} = 0 \text{ V}, f = 1 \text{ MHz}$		2.00		nF
C_{oes}	Output Capacitance			0.10		nF

Switching Characteristics

$t_{d(on)}$	Turn-on Delay Time	$V_{CC} = 600 \text{ V}, I_C = 15 \text{ A}, R_{Gon} = 40 \Omega, V_{GE} = \pm 15 \text{ V},$ Inductive Load	$T_J = 25^\circ\text{C}$		175	ns
			$T_J = 125^\circ\text{C}$		160	
t_r	Rise Time	$V_{CC} = 600 \text{ V}, I_C = 15 \text{ A}, R_{Gon} = 40 \Omega, V_{GE} = \pm 15 \text{ V},$ Inductive Load	$T_J = 25^\circ\text{C}$		50	ns
			$T_J = 125^\circ\text{C}$		55	
$t_{d(off)}$	Turn-off Delay Time	$V_{CC} = 600 \text{ V}, I_C = 15 \text{ A}, R_{Goff} = 40 \Omega, V_{GE} = \pm 15 \text{ V},$ Inductive Load	$T_J = 25^\circ\text{C}$		140	ns
			$T_J = 125^\circ\text{C}$		145	
t_f	Fall Time	$V_{CC} = 600 \text{ V}, I_C = 15 \text{ A}, R_{Goff} = 40 \Omega, V_{GE} = \pm 15 \text{ V},$ Inductive Load	$T_J = 25^\circ\text{C}$		245	ns
			$T_J = 125^\circ\text{C}$		380	
E_{on}	Turn-on Switching Loss	$V_{CC} = 600 \text{ V}, I_C = 15 \text{ A}, R_{Gon} = 40 \Omega, V_{GE} = \pm 15 \text{ V},$ $di/dt = 255 \text{ A}/\mu\text{s} (T_J = 125^\circ\text{C}),$ Inductive Load	$T_J = 25^\circ\text{C}$		1.74	mJ
			$T_J = 125^\circ\text{C}$		2.08	
E_{off}	Turn-off Switching Loss	$V_{CC} = 600 \text{ V}, I_C = 15 \text{ A}, R_{Goff} = 40 \Omega, V_{GE} = \pm 15 \text{ V},$ $du/dt = 2039 \text{ V}/\mu\text{s} (T_J = 125^\circ\text{C}),$ Inductive Load	$T_J = 25^\circ\text{C}$		0.63	mJ
			$T_J = 125^\circ\text{C}$		1.09	
Q_g	Total Gate Charge	$V_{GE} = +15 \text{ V} \dots -15 \text{ V}$	$T_J = 25^\circ\text{C}$		140	nC
RBSOA	Reverse Bias Safe Operation Area	$I_C = 30 \text{ A}, V_{CC} = 1050 \text{ V}, V_p = 1200 \text{ V}, R_g = 40 \Omega, V_{GE} = +15 \text{ V to } 0 \text{ V}, T_J = 150^\circ\text{C}$	Trapezoid			
SCSOA	Short Circuit Safe Operation Area	$V_{CC} = 600 \text{ V}, V_{GE} = 15 \text{ V}, T_J = 150^\circ\text{C}$	10			μs
$R_{\theta JC}$	IGBT Thermal Resistance: Junction-To-Case			0.73		$^\circ\text{C}/\text{W}$

Diode, Brake-Chopper
Maximum Rated Values ($T_C=25^\circ\text{C}$ unless otherwise specified)

V_{RRM}	Repetitive Peak Reverse Voltage	1200	V
I_F	Diode Continuous Forward Current	15	A
I_{FM}	Repetitive Peak Forward Current	30	A

Electrical Characteristics of FWD ($T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Description	Conditions	Min	Typ	Max	Unit
V_{FM}	Forward Voltage	$I_F=15\text{A}$	$T_J=25^\circ\text{C}$	2.00		V
			$T_J=125^\circ\text{C}$	2.20		
I_{rr}	Peak Reverse Recovery Current		$T_J=25^\circ\text{C}$	12		A
			$T_J=125^\circ\text{C}$	15		
Q_{rr}	Reverse Recovery Charge	$I_F=15\text{A}$, $-di_F/dt = 313\text{A}/\mu\text{s}(T_J=125^\circ\text{C})$, $V_R=600\text{V}$, $V_{GE}=-15\text{V}$	$T_J=25^\circ\text{C}$	0.94		μC
			$T_J=125^\circ\text{C}$	1.64		
E_{rec}	Reverse Recovery Energy		$T_J=25^\circ\text{C}$	0.37		mJ
			$T_J=125^\circ\text{C}$	0.76		
$R_{\theta JC}$	Diode Thermal Resistance: Junction-To-Case			1.19		$^\circ\text{C}/\text{W}$

Diode, Rectifier
Maximum Rated Values ($T_C=25^\circ\text{C}$ unless otherwise specified)

V_{RRM}	Repetitive Peak Reverse Voltage	$T_J = 25^\circ\text{C}$	1800	V
I_{FRMSM}	Maximum RMS Forward Current per Chip	$T_J = 80^\circ\text{C}$	35	A
I_{RMSM}	Maximum RMS Current at Rectifier Output	$T_J = 80^\circ\text{C}$	45	A
I_{FSM}	Surge Current @ $t_p=10$ ms	$T_J = 25^\circ\text{C}$	280	A
		$T_J = 150^\circ\text{C}$	250	
I^2t	I^2t - value	$T_J = 25^\circ\text{C}$	500	A^2s
		$T_J = 150^\circ\text{C}$	370	

Electrical Characteristics of Diode ($T_C=25^\circ\text{C}$ unless otherwise specified)

V_F	Forward Voltage	$I_F = 15 \text{ A}$	$T_J = 25^\circ\text{C}$	1.05			V
			$T_J = 150^\circ\text{C}$	1.00			
I_R	Reverse Current	$V_R=1200\text{V}$	$T_J = 25^\circ\text{C}$			1	mA
$R_{\theta JC}$	Diode Thermal Resistance: Junction-To-Case				0.89		$^\circ\text{C}/\text{W}$

Internal NTC-Thermistor Characteristics

R_{25}	$T_C = 25^\circ\text{C}$	5		k Ω
$\Delta R/R$	$T_C = 100^\circ\text{C}$, $R_{100} = 481\Omega$		± 5	%
P_{25}	$T_C = 25^\circ\text{C}$	50		mW
$B_{25/50}$	$R_2=R_{25} \exp[B_{25/50}(1/T_2-1/(298.15\text{K}))]$	3380		K
$B_{25/80}$	$R_2=R_{25} \exp[B_{25/80}(1/T_2-1/(298.15\text{K}))]$	3440		K

Module

Symbol	Description	Min	Typ	Max	Unit
V_{iso}	Isolation Voltage (All Terminals Shorted)	$f = 50\text{Hz}$, 1minute	2500		V
T_J	Maximum Junction Temperature			175	$^\circ\text{C}$
T_{JOP}	Maximum Operating Junction Temperature Range	-40		+150	$^\circ\text{C}$
T_{stg}	Storage Temperature	-40		+125	$^\circ\text{C}$
CTI	Comparative Tracking Index				
$R_{\theta CS}$	Case-To-Sink Thermally (Conductive Grease Applied)		0.05		$^\circ\text{C}/\text{W}$
T	Mounting Screw:M4	1.0		1.5	N·m
G	Weight		31		g




Fig.1 Typical Saturation Voltage Characteristics




Fig.2 Typical Output Characteristics




Fig.3 Forward Characteristics of FWD (Inverter)




Fig.4 Capacitance Characteristics




Fig.5 Typical Switching Loss vs. Collector Current




Fig.6 Typical Switching Loss vs. Gate Resistance




Fig.7 Typical Load Current vs. Frequency




Fig.8 Transient Thermal Impedance (IGBT)




Fig.9 Transient Thermal Impedance (Diode)




Fig.10 Typical Saturation Voltage Characteristics (Brake-Chopper)




Fig.11 Forward Characteristics of FWD (Brake-Chopper)




Fig.12 Forward Characteristics of Diode (Rectifier)




Fig.13 NTC Temperature Characteristics





Fig.14 Reverse Bias Safe Operation Area (RBSOA)


SilverMicro

Internal Circuit:



SilverMicro

Package Outline (Unit: mm):





Date	Revision	Notes
05/15/2018	01	Initial release

Announcement

Information in this document is believed to be accurate and reliable. However, NJSME does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to Make Changes

NJSME reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.