



GT25FF120A1H

IGBT Module

Features:

- Short Circuit Rated 10 μ s
- Low Saturation Voltage: $V_{CE(sat)} = 1.90V @ I_C = 25A, T_C=25^\circ C$
- Low Switching Loss
- 100% RBSOA Tested ($2 \times I_C$)
- Low Stray Inductance
- Lead Free, Compliant with RoHS Requirement



Applications:

- Industrial Inverters
- Servo Applications

IGBT, Inverter

Maximum Rated Values ($T_C=25^\circ C$ unless otherwise specified)

V_{CES}	Collector-Emitter Blocking Voltage		1200	V
V_{GES}	Gate-Emitter Voltage		± 20	V
I_C	Continuous Collector Current	$T_C = 80^\circ C,$	25	A
		$T_C = 25^\circ C$	50	A
I_{CM}	Repetitive Peak Collector Current	$T_J = 175^\circ C$	50	A
t_{SC}	Short Circuit Withstand Time		>10	μs
P_D	Maximum Power Dissipation per IGBT	$T_C = 25^\circ C$ $T_{Jmax} = 175^\circ C$	310	W

Electrical Characteristics of IGBT ($T_C=25^\circ\text{C}$ unless otherwise specified)

Static characteristics

Symbol	Description	Conditions	Min	Typ	Max	Unit
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C = 1 \text{ mA}, V_{CE} = V_{GE}$	5.0	5.5	6.0	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C = 25 \text{ A}, V_{GE} = 15 \text{ V}$	$T_J = 25^\circ\text{C}$	1.90	2.20	V
			$T_J = 125^\circ\text{C}$	2.20		V
I_{CES}	Collector-Emitter Leakage Current	$V_{GE} = 0 \text{ V}, V_{CE} = V_{CES}, T_J = 25^\circ\text{C}$			1	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE} = \pm 20 \text{ V}, V_{CE} = 0 \text{ V}, T_J = 25^\circ\text{C}$			100	nA
C_{ies}	Input Capacitance	$V_{CE} = 25 \text{ V}, V_{GE} = 0 \text{ V}, f = 1 \text{ MHz}$		3.3		nF
C_{oes}	Output Capacitance			0.19		nF

Switching Characteristics

$t_{d(on)}$	Turn-on Delay Time	$V_{CC} = 600 \text{ V}, I_C = 25 \text{ A}, R_G = 15 \Omega, V_{GE} = \pm 15 \text{ V},$ Inductive Load	$T_J = 25^\circ\text{C}$		140		ns
			$T_J = 125^\circ\text{C}$		140		
t_r	Rise Time		$T_J = 25^\circ\text{C}$		45		ns
			$T_J = 125^\circ\text{C}$		50		
$t_{d(off)}$	Turn-off Delay Time		$T_J = 25^\circ\text{C}$		165		ns
			$T_J = 125^\circ\text{C}$		170		
t_f	Fall Time		$T_J = 25^\circ\text{C}$		220		ns
			$T_J = 125^\circ\text{C}$		330		
E_{on}	Turn-on Switching Loss		$T_J = 25^\circ\text{C}$		1.76		mJ
			$T_J = 125^\circ\text{C}$		2.13		
E_{off}	Turn-off Switching Loss	$T_J = 25^\circ\text{C}$		1.02		mJ	
		$T_J = 125^\circ\text{C}$		1.72			
Q_g	Total Gate Charge	$T_J = 25^\circ\text{C}$		120		nC	
RBSOA	Reverse Bias Safe Operation Area	$I_C = 50 \text{ A}, V_{CC} = 1050 \text{ V}, V_p = 1200 \text{ V}, R_g = 15 \Omega, V_{GE} = +15 \text{ V to } 0 \text{ V}, T_J = 150^\circ\text{C}$	Trapezoid				
SCSOA	Short Circuit Safe Operation Area	$V_{CC} = 600 \text{ V}, V_{GE} = 15 \text{ V}, T_J = 150^\circ\text{C}$	10			μs	
$R_{\theta JC}$	IGBT Thermal Resistance: Junction-To-Case			0.475		$^\circ\text{C/W}$	

Diode, Inverter

Maximum Rated Values ($T_C=25^\circ\text{C}$ unless otherwise specified)

V_{RRM}	Repetitive Peak Reverse Voltage	1200	V
I_F	Diode Continuous Forward Current	25	A
I_{FM}	Diode Maximum Forward Current	50	A

Electrical Characteristics of FWD

Symbol	Description	Conditions	Min	Typ	Max	Unit
V_{FM}	Forward Voltage	$I_F = 25\text{A}$, $V_{GE} = 0\text{V}$	$T_J = 25^\circ\text{C}$	2.00	2.30	V
			$T_J = 125^\circ\text{C}$	2.20		
I_{rr}	Peak Reverse Recovery Current		$T_J = 25^\circ\text{C}$	15		A
			$T_J = 125^\circ\text{C}$	20		
Q_{rr}	Reverse Recovery Charge	$I_F = 25\text{A}$, $di/dt = 580\text{A}/\mu\text{s}$, $V_{rr} = 600\text{V}$, $V_{GE} = -15\text{V}$	$T_J = 25^\circ\text{C}$	1.05		μC
			$T_J = 125^\circ\text{C}$	2.19		
E_{rec}	Reverse Recovery Energy		$T_J = 25^\circ\text{C}$	0.39		mJ
			$T_J = 125^\circ\text{C}$	0.95		
$R_{\theta JC}$	Diode Thermal Resistance: Junction-To-Case			0.719		$^\circ\text{C}/\text{W}$

Internal NTC-Thermistor Characteristic

R_{25}	$T_C = 25^\circ\text{C}$	5		k Ω
$\Delta R/R$	$T_C = 100^\circ\text{C}$, $R_{100} = 481\Omega$		± 5	%
P_{25}	$T_C = 25^\circ\text{C}$	50		mW
$B_{25/50}$	$R_2 = R_{25} \exp[B_{25/50}(1/T_2 - 1/(298.15\text{K}))]$	3380		K
$B_{25/80}$	$R_2 = R_{25} \exp[B_{25/80}(1/T_2 - 1/(298.15\text{K}))]$	3440		K

Module

Symbol	Description		Min	Typ	Max	Unit
V _{iso}	Isolation Voltage(All Terminals Shorted)	f = 50Hz, 1minute	2500			V
T _J	Maximum Junction Temperature				175	°C
T _{JOP}	Maximum Operating Junction Temperature Range		-40		+150	°C
T _{stg}	Storage Temperature		-40		+125	°C
R _{θCS}	Case-To-Sink (Conductive Grease Applied)			0.1		°C/W
M	Mounting Screw:M3		1.5		2.0	N·m
G	Weight			30		g




Fig.1 Typical Saturation Voltage Characteristics




Fig.2 Typical Output Characteristics




Fig.3 Forward Characteristics of FWD




Fig.4 NTC Temperature characteristics




Fig. 5 Typical Switching Loss vs. Collector Current




Fig.6 Typical Switching Loss vs. Gate Resistance




Fig.7 Typical Load Current vs. Frequency




Fig.8 Reverse Bias Safe Operation Area (RBSOA)




Fig.9 Transient Thermal Impedance IGBT




Fig.10 Transient Thermal Impedance Diode






Fig.11 Capacitance Characteristics

Internal Circuit:



Package Outline (Unit: mm):



Announcement

Information in this document is believed to be accurate and reliable. However, NJSME does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to make changes

NJSME reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

SilverMicro