



# GT600CU65T9H-M

## IGBT Module

Preliminary Data

### Features:

- Field Stop Trench Gate IGBT
- Short Circuit Rated  $> 10\mu\text{s}$
- Low Saturation Voltage
- Low Switching Loss
- 100% RBSOA Tested ( $2 \times I_c$ )
- Copper Wire Bonding on Power Terminal
- Low Stray Inductance
- Lead Free, Compliant with RoHS Requirement



### Applications:

- UPS
- Servo Applications
- High Power Converters
- Motor Drives
- Wind Turbines

### IGBT, Brake-Chopper

**Maximum Rated Values**( $T_C=25^\circ\text{C}$  unless otherwise specified)

$V_{CES}$	Collector-Emitter Blocking Voltage		650	V
$V_{GES}$	Gate-Emitter Voltage		$\pm 20$	V
$I_C$	Continuous Collector Current	$T_C = 100^\circ\text{C}$	600	A
		$T_C = 25^\circ\text{C}$	1200	A
$I_{CM}$	Peak Collector Current Repetitive	$T_J = 175^\circ\text{C}$	1200	A
$t_{SC}$	Short Circuit Withstand Time		$> 10$	$\mu\text{s}$
$P_D$	Maximum Power Dissipation (IGBT)	$T_C = 25^\circ\text{C}$ $T_{Jmax}=175^\circ\text{C}$	2450	W

## Electrical Characteristics of Brake-chopper IGBT ( $T_C=25^\circ\text{C}$ unless otherwise specified)

### Static Characteristics

Symbol	Description	Conditions	Min	Typ	Max	Unit
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=12\text{mA}$ , $V_{CE}=V_{GE}$	5.00	5.90	6.80	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=600\text{A}$ , $V_{GE}=15\text{V}$	$T_J=25^\circ\text{C}$	1.50	1.70	V
			$T_J=125^\circ\text{C}$	1.70		V
			$T_J=150^\circ\text{C}$	1.70		V
$I_{CES}$	Collector-Emitter Leakage Current	$V_{GE}=0\text{V}$ , $V_{CE}=V_{CES}$ , $T_J=25^\circ\text{C}$			1	mA
$I_{GES}$	Gate-Emitter Leakage Current	$V_{GE}=\pm 20\text{V}$ , $V_{CE}=0\text{V}$ , $T_J=25^\circ\text{C}$			800	nA
$C_{ies}$	Input Capacitance	$V_{CE}=25\text{V}$ , $V_{GE}=0\text{V}$ , $f=1\text{MHz}$		44		nF
$C_{oes}$	output Capacitance			3.38		nF
$C_{res}$	Reverse Transfer Capacitance			1.81		nF

### Switching Characteristics

$t_{d(on)}$	Turn-on Delay Time	$V_{CC}=300\text{V}$ , $I_C=600\text{A}$ , $R_{Gon}=2\Omega$ , $V_{GE}=\pm 15\text{V}$ , Inductive Load	$T_J=25^\circ\text{C}$	0.52		$\mu\text{s}$
			$T_J=125^\circ\text{C}$	0.52		
			$T_J=150^\circ\text{C}$	0.53		
$t_r$	Rise Time		$T_J=25^\circ\text{C}$	0.37		$\mu\text{s}$
			$T_J=125^\circ\text{C}$	0.38		
			$T_J=150^\circ\text{C}$	0.39		
$t_{d(off)}$	Turn-off Delay Time		$T_J=25^\circ\text{C}$	0.46		$\mu\text{s}$
			$T_J=125^\circ\text{C}$	0.47		
			$T_J=150^\circ\text{C}$	0.48		
$t_f$	Fall Time	$T_J=25^\circ\text{C}$	0.21		$\mu\text{s}$	
		$T_J=125^\circ\text{C}$	0.24			
		$T_J=150^\circ\text{C}$	0.25			
$E_{on}$	Turn-on Switching Loss	$V_{CC}=300\text{V}$ , $I_C=600\text{A}$ , $R_{Gon}=2\Omega$ , $V_{GE}=\pm 15\text{V}$ , $di/dt=1350\text{A}/\mu\text{s}$ ( $T_J=150^\circ\text{C}$ ) Inductive Load	$T_J=25^\circ\text{C}$	14.8		mJ
			$T_J=125^\circ\text{C}$	17.5		
			$T_J=150^\circ\text{C}$	18.8		

E <sub>off</sub>	Turn-off Switching Loss	V <sub>CC</sub> =300V, I <sub>C</sub> =600A, R <sub>Goff</sub> =2Ω, V <sub>GE</sub> =±15V, du/dt=1766V/μs ( T <sub>J</sub> =150°C) Inductive Load	T <sub>J</sub> =25°C	58.1	mJ
			T <sub>J</sub> =125°C	62.8	
			T <sub>J</sub> =150°C	65.6	
Q <sub>g</sub>	Total Gate Charge	V <sub>GE</sub> =+15V...-15V	T <sub>J</sub> =25°C	3.77	μC
RBSOA	I <sub>C</sub> =1200A, V <sub>CC</sub> =600V, V <sub>p</sub> =650V, R <sub>Goff</sub> = 2Ω, V <sub>GE</sub> =+15V to 0V, T <sub>J</sub> =150°C			Trapezoid	
SCSOA	V <sub>CC</sub> = 300V, V <sub>GE</sub> = 15V, T <sub>J</sub> = 150°C			10	μs
R <sub>θJC</sub>	IGBT Thermal Resistance: Junction-To-Case(per leg)			0.061	°C/W

### Diode, Reverse

#### Maximum Rated Values of Diode (T<sub>C</sub>=25°C unless otherwise specified)

V <sub>RRM</sub>	Repetitive Peak Reverse Voltage	650	V
I <sub>F</sub>	Diode Continuous Forward Current	450	A
I <sub>FM</sub>	Diode Maximum Forward Current	900	A

#### Electrical Characteristics of Diode (T<sub>C</sub>=25°C unless otherwise specified)

Symbol	Description	Conditions	Min	Typ	Max	Unit	
V <sub>FM</sub>	Forward Voltage	I <sub>F</sub> =450A	T <sub>J</sub> =25°C	1.40		V	
			T <sub>J</sub> =125°C	1.45			
t <sub>rr</sub>	Reverse Recovery Time	I <sub>F</sub> =450A, -diF/dt =2100A/μs(T <sub>J</sub> =125°C), V <sub>R</sub> =300V, V <sub>GE</sub> =-15V	T <sub>J</sub> =25°C	0.21		μs	
			T <sub>J</sub> =125°C	0.29			
I <sub>rr</sub>	Peak Reverse Recovery Current		T <sub>J</sub> =25°C	155		A	
			T <sub>J</sub> =125°C	207			
Q <sub>rr</sub>	Reverse Recovery Charge		T <sub>J</sub> =25°C	12.8		μC	
			T <sub>J</sub> =125°C	24.5			
E <sub>rec</sub>	Reverse Recovery Energy		T <sub>J</sub> =25°C	0.37		mJ	
			T <sub>J</sub> =125°C	3.29			
R <sub>θJC</sub>	Diode Thermal Resistance: Junction-To-Case (per leg)			0.122		°C/W	



## Diode-Chopper

### Maximum Rated Values of Brake-chopper Diode ( $T_C=25^\circ\text{C}$ unless otherwise specified)

$V_{RRM}$	Repetitive Peak Reverse Voltage	650	V
$I_F$	Diode Continuous Forward Current	600	A
$I_{FM}$	Diode Maximum Forward Current	1200	A

### Electrical Characteristics of Brake-chopper Diode ( $T_C=25^\circ\text{C}$ unless otherwise specified)





Symbol	Description	Conditions	Min	Typ	Max	Unit
$V_{FM}$	Forward Voltage	$I_F=600\text{A}$	$T_J=25^\circ\text{C}$	1.80		V
			$T_J=125^\circ\text{C}$	1.75		
			$T_J=150^\circ\text{C}$	1.70		
$t_{rr}$	Reverse Recovery Time		$T_J=25^\circ\text{C}$	0.19		$\mu\text{s}$
			$T_J=125^\circ\text{C}$	0.27		
			$T_J=150^\circ\text{C}$	0.29		
$I_{rr}$	Peak Reverse Recovery Current	$I_F=600\text{A}$ , $-di_F/dt=1490\text{A}/\mu\text{s}(T_J=125^\circ\text{C})$ , $V_R=300\text{V}$ , $V_{GE}=-15\text{V}$	$T_J=25^\circ\text{C}$	84		A
			$T_J=125^\circ\text{C}$	155		
			$T_J=150^\circ\text{C}$	169		
$Q_{rr}$	Reverse Recovery Charge		$T_J=25^\circ\text{C}$	9.96		$\mu\text{C}$
			$T_J=125^\circ\text{C}$	25.58		
			$T_J=150^\circ\text{C}$	30.6		
$E_{rec}$	Reverse Recovery Energy	$I_F=600\text{A}$ , $-di_F/dt=1490\text{A}/\mu\text{s}(T_J=125^\circ\text{C})$ , $V_R=300\text{V}$ , $V_{GE}=-15\text{V}$	$T_J=25^\circ\text{C}$	1.92		mJ
			$T_J=125^\circ\text{C}$	5.12		
			$T_J=150^\circ\text{C}$	6.64		
$R_{\theta JC}$	Diode Thermal Resistance: Junction-To-Case (per leg)			0.119		$^\circ\text{C}/\text{W}$

## Internal NTC- Thermistor Characteristic

R <sub>25</sub>	T <sub>C</sub> =25°C	5		kΩ
ΔR/R	T <sub>C</sub> =100°C, R <sub>100</sub> =481Ω		±5	%
P <sub>25</sub>	T <sub>C</sub> =25°C	50		mW
B <sub>25/50</sub>	$R_2=R_{25} \exp[B_{25/50}(1/T_2-1/(298.15K))]$	3380		K
B <sub>25/80</sub>	$R_2=R_{25} \exp[B_{25/80}(1/T_2-1/(298.15K))]$	3440		K

## Module

Symbol	Description	Min	Typ	Max	Unit
V <sub>iso</sub>	Isolation Voltage (All Terminals Shorted)	f = 50Hz, 1minute	2500		V
L <sub>sCE</sub>	Stray Inductance Module		20		nH
T <sub>J</sub>	Maximum Junction Temperature			175	°C
T <sub>JOP</sub>	Maximum Operating Junction Temperature Range	-40		+150	°C
T <sub>stg</sub>	Storage Temperature	-40		+125	°C
CTI	Comparative Tracking Index	200			V
R <sub>θCS</sub>	Case-To-Sink Thermally (Conductive Grease Applied)		0.02		°C/W
M	Power Terminals Screw:M6	4.0		6.0	N·m
M	Mounting Screw:M6	4.0		6.0	N·m
G	Weight		300		g






Fig.5 Typical Switching Loss vs. Collector Current




Fig.6 Typical Switching Loss vs. Forward Current




Fig.7 Typical Switching Loss vs. Gate Resistance




Fig.8 Typical Switching Loss vs. Gate Resistance




Fig.9 Transient Thermal Impedance (IGBT)




Fig.10 Transient Thermal Impedance (Chopper Diode)




Fig.11 Capacitance Characteristics




Fig.12 NTC Temperature Characteristics








Fig.13 Forward Characteristics of Reverse Diode

### Internal Circuit



### Package Outline (Unit: mm):





Date	Revision	Notes
09/19/2019	01	Initial Release

### **Announcement**

Information in this document is believed to be accurate and reliable. However, NJSME does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

### **Right to Make Changes**

NJSME reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.