


GT75CU120B5H

IGBT Module

Preliminary Data

Features:

- Short Circuit Rated >10 μ s
- Low Saturation Voltage: $V_{CE(sat)} = 1.90V @ I_C = 75A, T_C = 25^\circ C$
- Low Switching Loss
- 100% RBSOA Tested ($2 \times I_C$)
- Low Stray Inductance
- Lead Free, Compliant with RoHS Requirement



Applications:

- Chopper Applications
- Servo Applications
- UPS System

IGBT, Brake-Chopper Maximum Rated Values ($T_C = 25^\circ C$ unless otherwise specified)

V_{CES}	Collector-Emitter Blocking Voltage		1200	V
V_{GES}	Gate-Emitter Voltage		± 20	V
I_C	Continuous Collector Current	$T_C = 80^\circ C,$	75	A
		$T_C = 25^\circ C$	75	A
I_{CM}	Repetitive Peak Collector Current	$T_J = 175^\circ C$	150	A
t_{SC}	Short Circuit Withstand Time		>10	μ s
P_D	Maximum Power Dissipation per IGBT	$T_C = 25^\circ C$ $T_{Jmax} = 175^\circ C$	520	W

Electrical Characteristics of IGBT ($T_C=25^\circ\text{C}$ unless otherwise specified)

Static characteristics

Symbol	Description	Conditions	Min	Typ	Max	Unit
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C = 1\text{mA}, V_{CE} = V_{GE}$	4.5	5.5	6.5	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C = 75\text{A}, V_{GE} = 15\text{V}$	$T_J = 25^\circ\text{C}$	1.90	2.10	V
			$T_J = 125^\circ\text{C}$	2.20		V
I_{CES}	Collector-Emitter Leakage Current	$V_{GE} = 0\text{V}, V_{CE} = V_{CES}, T_J = 25^\circ\text{C}$			1	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE} = \pm 20\text{V}, V_{CE} = 0\text{V}, T_J = 25^\circ\text{C}$			200	nA
C_{ies}	Input Capacitance	$V_{CE} = 25\text{V}, V_{GE} = 0\text{V}, f = 1\text{MHz}$		10.4		nF
C_{oes}	Output Capacitance			0.56		nF

Switching Characteristics

$t_{d(on)}$	Turn-on Delay Time	$V_{CC} = 600\text{V}, I_C = 75\text{A}, R_G = 15\ \Omega, V_{GE} = \pm 15\text{V},$ Inductive Load	$T_J = 25^\circ\text{C}$	190		ns
			$T_J = 125^\circ\text{C}$	170		
t_r	Rise Time		$T_J = 25^\circ\text{C}$	100		ns
			$T_J = 125^\circ\text{C}$	110		
$t_{d(off)}$	Turn-off Delay Time		$T_J = 25^\circ\text{C}$	270		ns
			$T_J = 125^\circ\text{C}$	280		
t_f	Fall Time		$T_J = 25^\circ\text{C}$	160		ns
			$T_J = 125^\circ\text{C}$	240		
E_{on}	Turn-on Switching Loss		$T_J = 25^\circ\text{C}$	5.77		mJ
			$T_J = 125^\circ\text{C}$	6.90		
E_{off}	Turn-off Switching Loss	$T_J = 25^\circ\text{C}$	3.54		mJ	
		$T_J = 125^\circ\text{C}$	5.60			
Q_g	Total Gate Charge	$T_J = 25^\circ\text{C}$	630		nC	
RBSOA	Reverse Bias Safe Operation Area	$I_C=150\text{A}, V_{CC}=1050\text{V}, V_p=1200\text{V}, R_g = 15\ \Omega, V_{GE}=\pm 15\text{V to } 0\text{V}, T_J = 150^\circ\text{C}$	Trapezoid			
SCSOA	Short Circuit Safe Operation Area	$V_{CC} = 600\text{V}, V_{GE} = 15\text{V}, T_J = 150^\circ\text{C}$	10			μs
$R_{\theta JC}$	IGBT Thermal Resistance: Junction-To-Case			0.29		$^\circ\text{C/W}$

Diode- Brake-Chopper
Maximum Rated Values ($T_C=25^\circ\text{C}$ unless otherwise specified)

V_{RRM}	Repetitive Peak Reverse Voltage	1200	V
I_F	Diode Continuous Forward Current	75	A
I_{FM}	Diode Maximum Forward Current	150	A

Electrical Characteristics of Diode ($T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Description	Conditions	Min	Typ	Max	Unit	
V_{FM}	Forward Voltage	$I_F = 75\text{A}$	$T_J = 25^\circ\text{C}$	2.00		V	
			$T_J = 125^\circ\text{C}$	2.20			
t_{rr}	Reverse Recovery Time	$I_F = 75\text{A},$ $di/dt = 750\text{A}/\mu\text{s},$ $V_{rr} = 600\text{V},$ $V_{GE} = -15\text{V}$	$T_J = 25^\circ\text{C}$	230		ns	
			$T_J = 125^\circ\text{C}$	300			
I_{rr}	Peak Reverse Recovery Current		$T_J = 25^\circ\text{C}$	35		A	
			$T_J = 125^\circ\text{C}$	40			
Q_{rr}	Reverse Recovery Charge		$T_J = 25^\circ\text{C}$	5.7		μC	
			$T_J = 125^\circ\text{C}$	9.52			
E_{rec}	Reverse Recovery Energy		$T_J = 25^\circ\text{C}$	1.92		mJ	
			$T_J = 125^\circ\text{C}$	3.80			
$R_{\theta JC}$	Diode Thermal Resistance: Junction-To-Case			0.45			$^\circ\text{C}/\text{W}$

Module

Symbol	Description	Min	Typ	Max	Unit
V _{iso}	Isolation Voltage (All Terminals Shorted) f = 50Hz, 1minute	2500			V
T _J	Maximum Junction Temperature			175	°C
T _{JOP}	Maximum Operating Junction Temperature Range	-40		+150	°C
T _{stg}	Storage Temperature	-40		+125	°C
R _{θCS}	Case-To-Sink Thermally (Conductive Grease Applied)		0.1		°C/W
T	Power Terminals Screw(M4)	0.5		1.5	N·m
T	Mounting Screw(M5)	0.5		1.5	N·m
G	Weight		32		g




Fig.1 Typical Saturation Voltage Characteristics




Fig.2 Typical Output Characteristics




Fig.3 Forward Characteristics of Diode




Fig.4 Capacitance Characteristics




Fig.5 Typical Switching Losses vs. Collector Current




Fig.6 Typical Switching Losses vs. Gate Resistance




Fig.7 Typical Load Current vs. Frequency




Fig.8 Reverse Bias Safe Operation Area (RBSOA)




Fig.9 Transient Thermal Impedance (IGBT)







Fig.10 Transient Thermal Impedance (Diode)

Internal Circuit:



Package Outline (Unit: mm):



Announcement

Information in this document is believed to be accurate and reliable. However, NJSME does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to Make Changes

NJSME reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

SilverMicro